

# FleeceBACK<sup>®</sup>

## Roofing Systems

Existing Asphaltic Roofing Materials	
Smooth	Yes (1)
Gravel	Yes (2) / No (6)
Mineral Cap Sheet	Yes
Granular Modified-Bitumen	Yes
Smooth Modified-Bitumen	Yes
Coal Tar	Yes (3)
Granular Modified Bitumen APP	Contact Carlisle
Smooth Modified Bitumen APP	No
Aluminum-Coated BUR	Yes (4)
Unweathered Asphalt	Yes/No

**Table Notes:**

(1) Existing Smooth BUR must be Type III or IV asphalt if the (Black) FleeceBACK EPDM, FleeceBACK PVC and KEE HP, or FleeceBACK TPO membrane is to be installed directly without insulation.

(2) A minimum 1/2" HP Recovery Board or insulation is required over properly prepared gravel BUR. FleeceBACK membrane cannot be installed directly over a gravel/slag surface.

(3) An insulation providing the necessary R-value must be specified to prevent the coal tar pitch from softening. FleeceBACK membranes cannot be installed directly to coal tar pitch.

(4) Any loose coatings must be removed by power-washing or by physical abrasion prior to the application of Flexible FAST Adhesive. A test installation over the aluminum-coated smooth BUR is recommended to ensure the aluminum coating is fully adhered.

(5) Splatter, 6" or 12" o.c. beads requires CAV-GRIP III for all applications. (6) Splatter Application NOT approved